



ALL-IN-ONE



MOBILITY



KIOSK



PANELS PC



PRINTERS



DISPLAYS



ACCESSORIES

[www.ares.com](http://www.ares.com)
**AURES**  
 TOUCH THE DIFFERENCE

# ODP 333

EPOS thermal receipt printer




Minimalist printer  
with splash-proof  
cubic design

*Specially designed for point of sale and service applications, the **ODP 333** by AURES is a thermal receipt printer which features a triple interface (including Ethernet) in a minimalist compact and cubic style, available in black or white.*

With its front receipt printout, it ensures optimum protection against dust, crumbs and liquid splashes in tough environments such as kitchens, restaurants, bars, bakeries and the like.

Thanks to its Energy Star certification, it switches automatically to stand-by mode in less than one second after it stops printing, allowing average power savings of at least 30% - embodying and thus respecting the values of Green IT.

The ODP 333 is perfectly compatible with Windows 10.



TOUCH THE DIFFERENCE

# ODP 333



Contemporary black or white cubic design

Highly compact ergonomic format

Low power motherboard

Integrated Triple interface (Serial RS 232C Serial, USB, & Ethernet)

Splash-proof receipt printout path located on the front side for enhanced protection; perfectly designed for all catering and hospitality sectors.

Configuration utilities

USB and RS232 cables included

Windows 10 compatible



| MODEL                 | ODP 333                                                                                  |
|-----------------------|------------------------------------------------------------------------------------------|
| Print method          | direct, thermal                                                                          |
| Print speed           | 160mm/sec                                                                                |
| Effective Print Width | 72mm / 512 dots/line                                                                     |
| Characters per line   | Font A: 42 columns, 180dpi<br>Font B : 56 columns, 180dpi / 64 columns, 203dpi           |
| Internal memory       | 64MB                                                                                     |
| Motherboard           | low power consumption - automatic standby mode<br>enables 30% less power use on average. |
| Paper loading         | automatic                                                                                |

| THERMAL PRINTER    |                    |
|--------------------|--------------------|
| Width:             | 79.5 mm +/- 0.5 mm |
| Thickness          | 0.065 - 0.1mm      |
| Max. roll diameter | 83mm               |

| CHARACTERS               |                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|
| Alphanumeric             | 95                                                                                  |
| Extended graphic         | 128 x 18 page                                                                       |
| International characters | 14                                                                                  |
| Barcodes                 | UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D PDF417, QR Code |
| Emulation                | ESC/POS compatible                                                                  |
| Drivers                  | Windows (XP, 2000, 2003, Vista, WEPOS) /OPOS / Linux / Java POS                     |
| Sensor                   | end-of-roll, near end-of-roll, cover open                                           |
| Till output port(s)      | 1 dual port (for 2 drawers) - RJ11 6-pin connector                                  |
| Interfaces               | Triple interface<br>RS232 Serial - USB & Ethernet dual (non-modifiable)             |
| Power supply             | External 24V - 2.5A                                                                 |

| PAPER CUTTER |                                        |
|--------------|----------------------------------------|
| Auto cutter  | guillotine type<br>Max. 30 cuts/minute |
| Cut type     | total or partial                       |

| OTHER FEATURES         |                                                                                                                                                     |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| MCBF                   | 35-50 million lines depending on type of use and paper thickness<br>Printer head lifespan: 160km<br>Paper cutter lifespan: Approx. 1.5 million cuts |
| Operating temperature  | -20 to +60°C                                                                                                                                        |
| Operating humidity     | 10% to 90% (without condensation)                                                                                                                   |
| Dimensions (D x W x H) | 165 x 135 x 105.02mm                                                                                                                                |
| Weight                 | 1kg approximately                                                                                                                                   |
| Colour                 | Black or white                                                                                                                                      |