

SRP-770II

4 inch Direct Thermal
Desktop Label Printer



Retail

Healthcare
&
PharmacyPost &
ParcelWarehouse &
Storage
Handling

Economic



All-in-one



BIXOLON SRP-770II can print 5 ips (127 mm/sec) and can recognize various programming languages such as SLCS, BPL-Z™, BPL-E™ automatically, and also the width of the paper can be adjusted easily to the range of 1.5~4.2 inch so that it can be used for barcode printing as well as receipt printing. The various on-board interfaces including Serial, Parallel, and USB allow flexible system configuration.

Specifications

PRINT CHARACTERISTICS

Print Method: Direct Thermal

Print Speed: Up to 5 ips (127 mm/sec)

Print Resolution: 203 dpi

Print Width: Up to 104 mm

Print Length: 6 ~ 304 mm

Media Sensor: Transmissive, Reflective, Head open

MEDIA CHARACTERISTICS

Media Type: Gap, Black Mark, Notch, Continuous, Fan-Fold

Media Width: 42 ~ 106 mm

Media Roll Diameter: Up to 130 mm

Media Roll Diameter: 0.06 ~ 0.20 mm

Supply Method: Easy Paper Loading

PHYSICAL CHARACTERISTICS

Dimensions (W x L x H): 184 x 221 x 171 mm
(7.24 x 8.70 x 6.73 inch)

Weight: 1.65 kg (3.63 lbs.)

Power: External Power Adaptor 100-240V AC, 50/60Hz

PERFORMANCE CHARACTERISTICS

Memory: 512KB SDRAM, 2MB FlashROM

Interface: Triple Interface
USB + Serial + Parallel

ENVIRONMENT CHARACTERISTICS

Temperature: Operating: 0 ~ 40°C (32 ~ 104°F)
Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity: Operating: 10 ~ 80% RH
Storage: 10 ~ 90% RH

SOFTWARE

Emulation: SLCS, BPL-Z™, BPL-E™

Driver: Windows Driver, Linux CUPS Driver, Mac Driver,
Virtual COM USB Driver, Utility Program, Label Artist™

SDK: Android SDK, Windows SDK

Fonts / Graphics / SYBLOGIES

Fonts: · 10 SLCS Resident Bitmap Fonts
· One SLCS Resident Scalable Font
· 23 Code Page

Graphics: Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbolologies:

1D: Codabar, Code 39, Code 93, EAN-8, EAN-13,
Interleaved 2-of-5, ITF, UCC/EAN-128, UPC-A, UPC-E
2D: Data Matrix, MaxiCode, PDF417, QR code (select two only)

OPTIONS

Auto Cutter

